Family list

1 application(s) for: JP2001225833 (A)

PAPER PACK WITH WINDOW FOR CHECKING AMOUNT OF RESIDUE

Inventor: KATAYAMA MASAMICHI; HAGIWARA Applicant: SANKYO CO; TOPPAN PRINTING KAZUYA CO LTD

EC: IPC: B65D5/40; B65D5/42; B65D5/52; (+6)

Publication JP2001225833 (A) - 2001-08-21 Priority Date: 2000-02-17

info: JP3817999 (B2) - 2006-09-06

Data supplied from the espacenet database - Worldwide

#### PAPER PACK WITH WINDOW FOR CHECKING AMOUNT OF RESIDUE

Publication number: JP2001225833 (A)

Also published as:

Publication date: 2001-08-21

DJP3817999 (B2)

Inventor(s): KATAYAMA

KATAYAMA MASAMICHI; HAGIWARA KAZUYA +

Applicant(s):

SANKYO CO: TOPPAN PRINTING CO LTD +

Classification:

865D5/40; 865D5/42; 865D5/52; 865D5/90; 865D5/42;


B65D5/44; (IPC1-7); B65D5/40; B65D5/42; B65D5/52

~ European:

Application number: JP20000039376 20000217 Priority number(s): JP20000039376 20000217

Abstract of JP 2001225833 (A)

PROBLEM TO BE SOLVED: To prevent, in a paper pack with a transparent window for visually checking the amount of residues of contents such as agricultural chemicals, the window from being broken so that the contents spill out during transportation. SOLUTION: Incised lines 3 are formed on a paperboard which forms a container body 1, and a removable cover part 2, in a longitudinally long shape, for forming a window is formed on the paperboard encircled by the lines 3. The cover part 2 is placed on a transparent sheet on the rear side of the part 2 to protect the transparent sheet, and in order to easily cut off the cover part 2, a peeling sheet 7 is heat sealed onto the entire area of the part 2 or onto an end of the part 2.



Data supplied from the espacenet database - Worldwide

# (19)日科(新許 (JP) (12) 公開特許公報 (A)

(11)特許出額公別番号 特開2001-225833 (P2001-225833A)

(43)公開日 平成13年8月21日(2001.8.21)

(51) Int.CL7		鐵別記号	PI		:	f-73-}*(参考)
865D	5/52	101	B65D	5/52	101D	3E060
	5/40			5/40	Z	
	5/42			5/42	В	

#### 審査請求 未請求 請求項の数2 OL (全 5 頁)


(21)出顯器号	(金額2000-38318(1-5000-38318)	(71)出額人	000001856
			三共株式会社
(22) 出職日	平成12年2月17日(2000.2.17)		東京都中央区日本機本町3丁目5巻1号
		(71)出藏人	000003193
			凸版印刷株式会社
			東京都台東区台東1丁目5番1号
		(72)発明者	片山 正道
			東京都中央区日本橋本町3丁目5番1号
			三共株式会社内
		(74)代理人	100067269
			<b>弁理士 佐野 路線</b>

## 最終頁に続く

#### (54) 【発明の名称】 残景篠駅用窓付紙パック

#### (57)【要約】

【課題】 透明な恋から農薬等の内容物の残量を提設で きるようにした残量確認用窓付紙バックにおいて、輸送 中などに窓が破れて内容物がこばれ出るのを防止する。 【解決手段】 容器本体1を構成する板板材に断続構造 の切れ目3を設け、この切れ目3で囲まれた紙板材部に 切除可能な窓形成用の除去カバー部2を綴裏帯状に形成 し、除去カバー部2裏側の透明シートに除去カバー部2 を重ねて透明シートを防護し、除去カバー部2の切除が より簡単に行えるように除去カバー部2の表面全域又は 除去カバー部の場部に、剥離用シート7をヒートシール した構成にする。



#### 【特許請求の範囲】

【請求項1】 紙板材を折り曲げ組み立てた南方体形状 の容器本体内に、液体、粉体等の内容物を収納すると もに、容器体体の一側面上下方向に縦長で、しかも透明 なシートによって全域が裏打ちされた窓を適して内容物 の理量を提認できるようにした残業確認用窓付載パック において

前記紙板材に前記窓の外形状に適合する断続構造の切れ 目を設け、この切れ目で開まれた紙板材部に切除可能な 窓形成用の除去カバー部を形成し、この除去カバー部の 素面全域又は除去カバー部の端部に、制能用シートを固 着したことを特徴とする投棄電取用窓付紙パック。

【請求項2】 前記測維用シートに、紙板村に固奪しない 協力部を設けたことを特徴とする請求項1に記載の残 豪譲退用窓付紙パック。

### 【発明の詳細な説明】

#### [0001]

【発明の属する技術分野】 この発明は、紙板材を折り 曲行で直方体形状に組み立て、内部に液体、粉体などの 内容物を収納する残量確認用窓付紙パックに係る技術分 撃に騒する。

#### [0002]

【従来の技術】 従来、紙パックの中に、内部に、たと えば溶状の農薬を収納したものがあるが、農薬を一度に 全部使い切らないときは、そのまま保管して後の使用に 備える場合がある。

【0003】したがって、そのように内容物を軽パック で保管する場合には、後に再び使用するときに、内容物 の発量を確認できると便利である。そのため、後来の紙 パックの中には、高さ方向に相長い窓孔を設付、その窓 孔を週刊マルルで裏打ちして透明な窓を形成し、その 窓から内容物の発量を視弦できるようにしたものがある (たとよば歌即マ3・93298号報照)、

# [0004]

【発明が解決しようとする課題】 上述のような従来の 残量確認用窓付紙バックでは、たとえば輸送中に、透明 フィルムに不用意に尖ったものが当たると、その透明フ ィルムが破れて窓から付容物がこばれ出てしまうという 課題があった。

[0005] そこで、この発明の目的は、上述のように 透明な窓から内容物の残量を視認できるようにした残量 確認用窓付級パックにおいて、たとえば輸送中に窓が破 れて内容物がこばれ出るのを防止することにある。

#### [0006]

【課題を解決するための手段】 上記目的は、紙板材を 折り曲げ組み立てた直方体形状の容器本体内に、液体。 粉体等の内容物を収納するとともに 容器本体の一層面 上下方向に縦長で、しかも透明なシートによって全域が 異打ちされた窓を達して内容物の残量を模器できるよう にした残量磁器用窓付近パックにおいて、解記紙板材に 前能窓の外形状に適合する断結構造の切れ目を設け、こ の切れ目で囲まれた紙板材能に切除可能な窓形成用の除 去カバー部を形成し、この除去カバー部の表面全域又は 除去カバー部の場部に、刺離用シートを固着したことに より達成される。

【0007】上記目的は、前記刺離用シートに、紙板材 に固着しない議み部を設けたことにより達成される。

# [0008]

【発明の実施の形態】 以下、図面を参照しつつ、この 発明の実施の形態について説明する。

【〇〇〇】図1は、この希明による残量確定用窓付託 バックを示す。図中符号1は、この紙バックの密器本体 である、密緒本体1は、シート状の紙板材を折り曲げて 直方体状に組み立て、内部に内容物として液状の農薬を 収納するものである。なお、容器本体1内に収納する内 空物は、この農薬等の液体に限らず、物体などであって もよいのは効動である。

【0010】さて、容器本体1を構成する低級材は、 売省略するが、たとえば(表開)PE/紙/PE/シリ カ素着PET/PE(裏開)からなる層積板で、剛性を もたせた構造になっている。また、たとえば(表関)P E/紙/PE/AL/PET/PE(裏側)の層精成と することもできる。

【0011】そして、窓路本体1の…明度11には、上 下方向に継長な替状の除去カバー部2を設ける。除去カ バー部2は、その外間縁に治って抵板材に財産構造の切 れ目3を入れて、この切れ目3で囲まれた紙板材部を切 除可能に形成している。その場合、例えば頻宜核刃を用 いの厚を方向に貫通するように形成する。 材の厚を方向に貫通するように形成する。

【0012】切れ目3は、図3(a)に示すように、その1つ1つをやや長い線状に形成するとよい。

【0013】なお、切れ目3は、図3(b)に示すよう に、上下両端陽を除いて、その1つ1つを領・確線状に 形成してもよい。また、たとよば図3(c)に示すよう に、1つ1つの切は目3を、上端を内向きに曲針た略一 形成に形成したものであってもよい。

【0014】一方、この紙パックは、図2に示すように、除去カバー部2の真葉懸を除く紙板材の裏面に、透明シート4をヒートシール4 4 する、透明シート44は、たとえば【外側】PE/Nッ/シリカ蒸着PET(内側】からなる層構版で、パリア性を高かた構造にしている。そして、この透明シート4年除去が「一部2に重わて設け、切た日3を実際からシールしている。また、透明シート4は、たとえば【外側】PE/OPP/シリカ素者PET(内側)の層構成とした部村で形成することもできる。

【0015】なお、上述した本発明による紙パックには、図1に示すように、除去カバー部2の側縁に農薬の 残量を示す日盛5を設けている。 【0016】さらに、この紙パックは、除去かバー部2 の切除がより簡単に行えるように、関4でも示すよう に、除去カバー部2の表面関に剥離用シート7を備えた 構成にする。

【0017】剥離用シートでは、たとえば「外順)Ny PE「内側)の層様はにした透明な解長シートを用 い、図5(a)・(b)・(c)にそれぞれデオよう に、除去かバー部2の表面を域にレートシールアもして 園着する。その場合、剥離用シート7をより強く園着す べく、耐電板炒を用いて切れ目3を入れる幅に、除去か バー部2の審決表面部を、予めニス抜きしておくとよ

【0018】 刺離用シートアとしては、たとえば(外側)のPP/PE【内側】 「外側)Ny/AL/PE (内側)、「外側)のPP/AL/PE(内側)、「外側)のPP/AL/PE(内側)、「外側)のPP/AL/PE(内側)の層構成とした、それぞれ他のシート材を用いることもできる。

【0019】なお、そのような劉麗用シートでには、上 部関に橋み第7aを設ける。その橋み第7aは、指で橋 みやすいように、前記紙板材に対しヒートシールなどし て甾礬しないようにする。

【0020】をて、上述した構成の残量確認用影件紙が、 ックでは、その中に農薬を収納して保管したり、輸送し たりする。そのような場合、影響シート4の実験は、除 去カバー部2を重ねて防護しているため、不用窓に尖っ たものが当たっても途明シート4が彼れて農薬がこぼれ 出るのを掛けできる。

【0021】そして、あとて、この紙パック内の農薬を 使用する場合、その農薬の残産を確認する必要があると きは、剥離用シートアの納予第7をを摘んで剥離用シー トアを引っ張り、それと一体に除去カバー部2を切れ目 3に沿って切除し、透明を常状の窓を外端に磨ませる。 そして、目底5を見て残量を確認する。

【0022】なお、図珠した例において、制龍用シート 7は、除去がバー部2と重なる中央部分でヒートシール し、その外側部分はヒートシールしていない。しかし、 図示しないが、剥離用シート7の企画をヒートシールし てもよい、その場合、剥離用シート7の中央部分は強め に除去かバー部2に固着され、外側部分はバイグロスニ スのために認かに固著される。

【0023】また、上述した何では、除去カバー都2の 表面全域に制能用シートフを固着したが、関6(a)・ (b)・(c)にそれぞれ示すように、除去カバー部2 表面の上端部にだけ制能用シートフを固着するようにし てもよい。

【0024】図6の例では、剥離用シート7として、た とえば解記したように「外側」 Nッ/ア E 【内側」の欄 構成にした適明な小片シートを用いてヒートシール7 c する。そして、農薬残量を確認する必要があるときは、 同様に摘み部7 a を指んて剥離用シート7を引っ張り、 それと一体に除去カバー部2全体を切れ目3に沿って切除する。

【0025】なお、除去カバー部2表面の下端部に剥離 用シート7を固着して除去カバー部2を切除するように してもよい。上述した剥離用シート7は、必ずしも適明 でなくてもよいのは勿論である。

【0026】 ここで、歯部の説明中で用いた記号について説明する。 PEはポリエチレン、A Jはアルミニウム 宿、PETはポリエチレンテレフタレート、Nyはナイ ロン、OPPは延伸ポリプロピレンを表わす。 【0027】

【発明の効果】 上述した本発明によれば、次のような 効果が得られる。

切ができない。 【00281 請求項1によれば、紙板材に断続構造の切れ目を設け、この切れ目で囲まれた紙板材部に切除可能 た窓形成用が除去が、一部を形成し、透明シートの表側 の際などに、不用窓に尖ったものなどが当たっても透明 シートが破れて内容物がこばれ出るのを防止することが できる。また、除去が、一部の残而全域又は除去が、 できる。また、除去が、一部の残而全域又は除去が、 のの増都に刺縦用シートを固定した構成とすることによ り、内容物の残量を確認する必要があるとき、制能用シートを引っ張るだけで、簡単に除去が、一部で切れ目に沿って できる。それ、除去が、一部を切れ目に沿って できる。それて、除去が、一部を切れ目に沿って では、「原料に消費が必要を外部に臨ませれば、簡単に残量を根 認することができる。それに臨ませれば、簡単に残量を根 認することができる。

【0029】請求項2によれば、加えて、制徳用シート に、張原杯に周緒しない場本部を設けた構成とし、これ により、除去かバー部を切除するとき、この補み部を補 んで剥離用シートを簡単に引っ張ることができる。 【四面の簡単な説明】

【図1】 本発明による残量確認用急付紙バックの一例 を示す終視図である。

【図2】 その紙バックの窓部構造を示す部分横断面図である。

【図3】 除去カバー部の外周縁に設ける切れ目形状を 示す構成説明図である。


【図4】 除去カバー部に剥離シートを固着した窓部構造を示す部分横断面図である。


【図5】 除去カバー部の表面全域に剥離シートを固着 した窓部構造の構成説明図である。

【図6】 除去カバー部表面の上端部に剥離シートを置 着した窓都構造の構成説明団である。


### 【符号の説明】

- ・ 容器本体? 除去カバー部
- 3 切れ目
- 4 透明シート
- 7 剥離用シート
- 7 a 摘み部









フロントページの続き

(72)発明者 教原 一也 東京都台東区台東1丁目5番1号 凸版印 朝株式会社内 Fターム(参考) 3E060 A405 CB07 CE05 CE07 CE13 CE18 CE19 CE30 DA22 DA30 EA03 EA04

# PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2001-225833

(43)Date of publication of application: 21.08.2001

(51)Int.Cl.

865D 5/52 865D 5/40 865D 5/42

(21)Application number: 2000-039376

(21)Application manie

(71)Applicant : SANKYO CO LTD

17

(water

(22)Date of filing:

17.02.2000

(72)Inventor: KATAYAMA MASAMICHI

HAGIWARA KAZUYA

TOPPAN PRINTING CO I TD


(54) PAPER PACK WITH WINDOW FOR CHECKING AMOUNT OF RESIDUE

(57)Abstract:

PROBLEM TO BE SOLVED: To prevent, in a paper pack with a transparent window for visually checking the amount of residues of contents such as agricultural chemicals, the window from being broken so that the contents spill out during

transportation.

SOLUTION: Incised lines 3 are formed on a paperboard which forms a container body 1, and a removable cover part 2, in a longitudinally long shape, for forming a window is formed on the paperboard encircled by the lines 3. The cover part 2 is placed on a transparent sheet on the rear side of the part 2 to protect the transparent sheet, and in order to easily cut off the cover part 2, a peeling sheet 7 is heat sealed onto the entire area of the part 2 or onto an end of the part 2.



JPO and INPIT are not responsible for any damages caused by the use of this translation.

- 1. This document has been translated by computer. So the translation may not reflect the original precisely.
- 2.\*\*\* shows the word which can not be translated.

3.In the drawings, any words are not translated.

#### CLAIMS

# [Claim(s)]

[Claim 1]While storing contents, such as a liquid and a granular material, in a package body of rectangular parallelepiped shape which bent and assembled paper board material, In a windowed paper pack for a residue check which spaces a window with which it was longwise to a one side face sliding direction of a package body, and the whole region was moreover backed with a transparent sheet, and enabled it to recognize a residue of contents visually, A windowed paper pack for a residue check having provided a break of intermittence structure which suits outline shape of said window in said paper board material, having formed a resectable removal cover part for fenestration in a paper board material part surrounded by this break, and adhering a sheet for exfoliation to the surface whole region of this removal cover part, or an end of a removal cover part.

[Claim 2]The windowed paper pack for a residue check according to claim 1 providing a knob part which does not adhere to paper board material in said sheet for exfoliation.

JPO and INPIT are not responsible for any damages caused by the use of this translation.

- 1. This document has been translated by computer. So the translation may not reflect the original precisely.
- 2.\*\*\*\* shows the word which can not be translated.
- 3.In the drawings, any words are not translated.

#### DETAILED DESCRIPTION

# [Detailed Description of the Invention]

[0001]

[Field of the Invention] This invention bends paper board material, assembles it to rectangular perallelepiped shape, and belongs to the technical field concerning the windowed paper pack for a residue check which stores contents, such as a liquid and a granular material, inside. [0002]

[Description of the Prior Art]Although some which stored liquefied agricultural chemicals inside, for example are in a paper pack conventionally, when all not exhausting agricultural chemicals at once, it may be keet as it is and may prepare for next use.

[0003] Therefore, in keeping contents with a paper pack such, when using it again behind, it is convenient if you can check the residue of contents. Therefore, a long and slender window hole is established in a height direction, the window hole is backed with a bright film, a transparent window is formed, and there are some conventional paper packs which enabled it to recognize the residue of contents visually from the window (for example, refer to application—for—utility—model—registration common [ No. 93298 / three to ]).

# [0004]

[Problem to be solved by the invention] In the above conventional windowed paper packs for a residue check, SUBJECT that the bright film is torn, and contents will fall and it will come out from a window, for example during transportation if what sharpened carelessly hits a bright film occurred. [0005] Then, in the windowed paper pack for a residue check which enabled it to recognize the residue of contents visually from a window transparent as mentioned above, the purpose of this invention is to prevent a window being four during transportation, and contents falling and coming out.

#### [8000]

[Means for solving problem]While the above-mentioned purpose stores contents, such as a liquid and a granular material, in the package body of the rectangular parallelepiped shape which bent and assembled paper board material. In the windowed paper pack for a residue check which spaces the window with which it was longwise to the one side face sliding direction of the package body, and the whole region was moreover backed with the transparent sheet, and enabled it to recognize the residue of contents visually. The break of the intermittence structure which suits the outline shape of said window is provided in said paper board material, the resectable removal cover part for fenestration is formed in the paper board material part surrounded by this break, and it is attained by having adhered the sheet for exfoliation to the surface whole region of this removal cover part, or the end of a removal cover part. [0007]The above-mentioned purpose is attained by having provided the knob part which does not adhere to said sheet for exfoliation at paper board material.

#### [80000]

[Mode for carrying out the invention]Hereafter, this embodiment of the invention is described, referring to Drawings.

[0009] <u>Drawing 1</u> shows the windowed paper pack for a residue check by this invention. The mark 1 in a figure is a package body of this paper pack. The package body 1 bends sheet shaped paper board material, assembles it to rectangular parallelepiped shape, and stores agricultural chemicals liquefied as contents inside. As for the contents stored in the package body 1, it is needless to say that it may be able to the package body 1 in the package body 1 in

[0010]now — although it carries out figures omitted abbreviated [ of the paper board material which constitutes the package body 1 ] — for example [A side front] PE / paper / PE / silica vacuum evaporation PET/PE [The back side] By lamination, \*\* and others, it has structure which gave rigidity. For example[A side front] PE / paper / PE/AL/PET/PE It can also be considered as lamination on the [back side].

[0011] And the band-like removal cover part 2 longwise to a sliding direction is formed in the one side face I a of the package body 1. The removal cover part 2 puts the break 3 of intermittence structure into paper board material along that periphery edge, and forms a paper board material part surrounded by this break 3 resectable. In that case, paper board material is suitably cut using a punching blade, for example, and it forms so that the break 3 may be penetrated to a thickness direction of paper board material, as shown in drawing 2.

[0012] The break 3 is good to form the each in a little long line, as shown in drawing 3 (a).

[0013] The break 3 may form the each in the shape of [ short ] a dashed line except for the top-and-bottom-ends side, as shown in <u>drawing 3 (b)</u>. As shown, for example in <u>drawing 3 (c)</u>, each break 3 may be formed in the abbreviation \*\* form where the upper bed was bent for inner.

[0014]heat-sealing 4a On the other hand, this paper pack makes the transparent sheet 4 the rear face of the paper board material except the back side of the removal cover part 2, as shown in <u>drawing 2</u>, the transparent sheet 4 — for example [Outside] PE/Ny / silica vacuum evaporation PET [Inside] By the lamination, \*\* and others, it is made the structure which improved barrier property. And this transparent sheet 4 is formed in the removal cover part 2 in piles, and the seal of the break 3 is carried out from the back side, the transparent sheet 4 — for example [Outside] PE/OPP / silica vacuum evaporation PET It can also form by the component made into [inside] lamination.

[0015] As shown in drawing 1, the graduation 5 which shows the residue of agricultural chemicals to the side edge of the removal cover part 2 is provided in the paper pack by this invention mentioned above. [0016] As drawing 4 also shows, this paper pack is made the composition which equipped the surface side of the removal cover part 2 with the sheet 7 for exfoliation so that excision of the removal cover part 2 can carry out more easily.

[0017]the sheet 7 for exfoliation — for example [Outside] Ny/PEUsing the transparent longwise sheet made into [inside] lamination, as shown in drawing 5 (a) — (b) — (c), respectively, it heat—sealing 7b Carries out throughout the surface of the removal cover part 2, and adheres. In that case, before putting in the break 3 using said punching blade, it is [ that the sheet 7 for exfoliation should be adhered more strongly ] good to carry out varnish omission of the band–like surface part of the removal cover part 2 heforehand.

[0018]as the sheet 7 for exfoliation — for example [Outside] OPP/PE[Inside] \*\*[Outside] Ny/AL/PE [Inside] \*\*[Outside] OPP/AL/PE[Inside] \*\*[Outside] PET/AL/PEThe web material of others respectively made into [inside] lamination can also be used.

[0019]The knob part 7a is formed in such a sheet 7 for exfoliation at the upper part side. The knob part 7a is kept from adhering by heat sealing to said paper board material so that it may be easy to gather with a finger.

[0020]Now, in the windowed paper pack for a residue check of composition of having mentioned above, into it, agricultural chemicals are stored, and are kept or conveyed. In such a case, since the side front of the transparent sheet 4 protects the removal cover part 2 in piles, even if what sharpened carelessly hits, it can prevent the transparent sheet 4 being torn, and agricultural chemicals falling and coming out. [0021]And when using the agricultural chemicals in this paper pack and it is necessary to check the residue of those agricultural chemicals, the knob part 7a of the sheet 7 for exfoliation is gathered, the sheet 7 for exfoliation is gathered, the sheet 7 for exfoliation is pulled, the removal cover part 2 is excised along with the break 3 to it and one, and a transparent band-like window is made to face outside later. And the graduation 5 is seen and a residue is checked.

[0022] In the illustrated example, the sheet 7 for exfoliation is heat sealed by the center portion which laps with the removal cover part 2, and has not heat sealed the lateral part. However, although not illustrated, the whole surface of the sheet 7 for exfoliation may be heat sealed. In that case, the center portion of the sheet 7 for exfoliation adheres strength at the removal cover part 2, and a lateral part adheres weakness for by gross varnish.

[0023] Although the sheet 7 for exfoliation was adhered throughout the surface of the removal cover

cover part 2 surface in the example mentioned above, as shown in <u>drawing 6</u> (a) –(b) – (c), respectively. [0024]In the example of <u>drawing 6</u>, it described above as the sheet 7 for exfoliation, for example. [Outside] Ny/PEheat-sealing 7c Garry out using the transparent wafer sheet made into linside] lamination. And when it is necessary to check an agricultural-chemicals residue, the knob part 7a is gathered similarly, the sheet 7 for exfoliation is pulled, and the removal cover part 2 whole is excised along with the break 3 to it and one.

[0025]The sheet 7 for exfoliation is adhered to the lower end part of the removal cover part 2 surface, and it may be made to excise the removal cover part 2. As for the sheet 7 for exfoliation mentioned above, it is needless to say that may not necessarily be transparent.

[0026] Here, a sign which is during the aforementioned explanation and was used is explained. In PE, as for polyethylene and aluminum, aluminium foil and PET express polyethylene terephthalate, Ny expresses nylon, and OPP expresses extension polypropylene.

[Effect of the Invention]According to this invention mentioned above, the following effects are acquired. [0028]Since it is the composition which provided the break of intermittence structure in paper board material, formed the resectable removal cover part for fenestration in the paper board material part surrounded by this break, and protected the removal cover part in piles on the side front of the transparent sheet according to Claim 1, It can prevent a transparent sheet being torn, and contents falling and coming out in the case of transportation, etc., even if what sharpened carelessly hits. When it is necessary to check the residue of contents by making the sheet for exfoliation the surface whole region of a removal cover part, or the end of a removal cover part that the composition which adhered, a removal cover part can be easily excised only by pulling the sheet for exfoliation. And if a removal cover part is excised along with a break and a transparent window is made to face outside, a residue can be recognized visually easily.

[0029]When according to Claim 2 it has composition which provided the knob part which does not adhere to paper board material and this excises [in addition] a removal cover part on the sheet for exfoliation, this knob part can be gathered and the sheet for exfoliation can be pulled easily.

JPO and INPIT are not responsible for any damages caused by the use of this translation.

- 1. This document has been translated by computer. So the translation may not reflect the original precisely.
- 2.\*\*\*\* shows the word which can not be translated.
- 3.In the drawings, any words are not translated.

#### TECHNICAL FIELD

[Field of the Invention] This invention bends paper board material, assembles it to rectangular parallelepiped shape, and belongs to the technical field concerning the windowed paper pack for a residue check which stores contents, such as a liquid and a granular material, inside.

JPO and INPIT are not responsible for any damages caused by the use of this translation.

- 1. This document has been translated by computer. So the translation may not reflect the original precisely.
- 2.\*\*\*\* shows the word which can not be translated.
- 3.In the drawings, any words are not translated.

#### DESCRIPTION OF DRAWINGS

[Brief Description of the Drawings]

[Drawing 1] It is a perspective view showing an example of the windowed paper pack for a residue check by this invention.

[Drawing 2]It is a partial cross-sectional view showing the window part structure of the paper pack. [Drawing 3]It is a composition explanatory view showing the break form provided in the periphery edge of a removal cover part.

Drawing 4 It is a partial cross-sectional view showing the window part structure which adhered the exfoliation sheet to the removal cover part.

Drawing 5]It is a composition explanatory view of the window part structure which adhered the exfoliation sheet throughout the surface of a removal cover part. Drawing 6]It is a composition explanatory view of the window part structure which adhered the


exfoliation sheet to the upper bed part of the removal cover part surface.


- [Explanations of letters or numerals]
  1 Package body
- 2 Removal cover part
- 3 Break
- 4 Transparent sheet
- 7 The sheet for exfoliation
- 7a Knob part

JPO and INPIT are not responsible for any damages caused by the use of this translation.


- 1. This document has been translated by computer. So the translation may not reflect the original precisely.
- 2.\*\*\*\* shows the word which can not be translated.
- 3.In the drawings, any words are not translated.


### DRAWINGS





[Drawing 3]





[Translation done.]